



Fabric Specification Sheet

VT18008-50

18oz/yd² balanced 0/90 glass w/ .75oz/ft² chop mat

Total Weight:

25.21 oz/yd²

854.85 g/m²

Roll Details

50 Inches

1270.00 MM

219 Pounds per roll

99.48 KG per roll

100 Yards per roll

300.00 FT per roll

3 " Core

Shrink wrapped 9 Rolls per Pallet

Stitching Details

150 denier Polyester Yarn

7 CPI

3.63 mm stitch length

0.54 oz/yd²

2.15% of Total AW

0° 35.54% of Total AW

E-glass fiber

303.81 g/m²

8.96 oz/yd²

(-)45° 0.00% of Total AW

0.00 g/m²

0.00 oz/yd²

90° 35.54% of Total AW

E-glass fiber

303.81 g/m²

8.96 oz/yd²

(+)45° 0.00% of Total AW

0.00 g/m²

0.00 oz/yd²

MAT/VEIL: 26.77% of Total AW

Chopped Strand Mat

0.75 oz/ft²

228.87 g/m²

6.75 oz/yd²

V2 Composites, Inc. makes no warranties, expressed or implied, including merchantability or fitness for a particular purpose, except as expressly stated in writing.

770 Lee Road 191
Auburn, Alabama 36830

P: 334.502.3000
F: 334.502.3088

www.v2composites.com