



Fabric Specification Sheet

VT36010-50

36oz/yd2 balanced 0/90 glass w/ chop

Total Weight: 45.78 oz/yd² 1552.12 g/m²

Roll Details	
50 Inches	1270.00 MM
477 Pounds per roll	216.74 KG per roll
100 Yards per roll	300.00 FT per roll
3 " Core	
Shrink wrapped 9 Rolls per Pallet	

Stitching Details	
100 denier	Polyester Yarn
7 CPI	3.63 mm stitch length
0.36 oz/yd ²	0.79% of Total AW

0° 40.40% of Total AW

E-glass fiber	627.12 g/m ²	18.50 oz/yd ²	
0	0.00 g/m ²	0.00 oz/yd ²	

MAT/VEIL: 0.00% of Total AW

0	0.00 oz/ft ²	0.00 g/m ²	0.00 oz/yd ²
---	--------------------------------	------------------------------	--------------------------------

(-)45° 0.00% of Total AW

0	0.00 g/m ²	0.00 oz/yd ²	
0	0.00 g/m ²	0.00 oz/yd ²	

90° 39.15% of Total AW

E-glass fiber	607.61 g/m ²	17.92 oz/yd ²	
0	0.00 g/m ²	0.00 oz/yd ²	

(+)45° 0.00% of Total AW

0	0.00 g/m ²	0.00 oz/yd ²	
0	0.00 g/m ²	0.00 oz/yd ²	

MAT/VEIL: 19.66% of Total AW

E-glass fiber	1.00 oz/ft ²	305.16 g/m ²	9.00 oz/yd ²
---------------	--------------------------------	--------------------------------	--------------------------------

V2 Composites, Inc. makes no warranties, expressed or implied, including merchantability or fitness for a particular purpose, except as expressly stated in writing.

770 Lee Road 191
Auburn, Alabama 36830

P: 334.502.3000
F: 334.502.3088

www.v2composites.com